



SureColor® S60600





Signage

SureColor S-Series

A performance benchmark has been set.

Value — affordable 64" roll-to-roll signage printer

Advanced printhead technology — Dual Epson® PrecisionCore® TFP® printhead technology to meet the needs of high-demand production environments

High-speed performance — outdoor production speeds up to 550 sq ft/hr and indoor-quality production speeds up to 310 sq ft/hr¹

UltraChrome® GS3 Ink — proven 4-color solvent-based ink system

Extreme value — low initial investment with high productivity

One solution for your printing needs — includes workflow software by ONYX®, substrate support system, and one-year on-site limited warranty

Productivity — Epson Precision Dot technology allows for band free printing at high speeds

Easy media setup — Set up new media in minutes

Simple Maintenance — Fabric wiper & air filtration system to ensure continuous, reliable production



SureColor® S60600

Printing Technology Dual Advanced PrecisionCore® TFP® 8-channel, drop-on-demand, inkjet printhead with ink-repelling coating technology

Ink Type UltraChrome GS3

Production Edition Ink Configuration (x2): C, M, Y, K **Droplet Technology** Smallest droplet size: 4.2 picoliters;

Variable Droplet Technology can produce up to three different

Maximum Resolution 1440 x 1440 dpi; 1440 x 720 dpi; 720 x 720 dpi; 720 x 360 dpi

Printer Speed¹ Vinyl Banner 1020 sa ft/hr Draft: N/A Production: 550 sq ft/hr 310 sq ft/hr Quality: 310 sq ft/hr 190 sa ft/hr

Printer Language/Drivers Epson ESC/P® raster Nozzle Configuration Color and Monochrome Heads 1440 nozzles per color

Epson Ink Supply System²

Cartridge Fill Volume 700 mL x 4 colors total

Ink Cartridge 2 years from printed

Shelf Life Production date or 6 months after opened

Roll Media Handling

Media Input Single roll-to-roll

Cut-sheet Size 17" x 22" up to 64" wide

Media Core 2" or 3" core

Input Roll Diameter Up to 9.8'

Input Roll Weight Up to 95 lb Media Thickness From 45 gsm up to 1 mm thick

Take Up Reel Fully automatic "wind in" or "wind out" with tension bar

Output Roll Weight Up to 95 lb

Media Heating System

Pre Heater Off or 86° to 122°F Platen Heater Off or 86° to 122°F

Post Heater Off or 86° to 131°F

Independently controlled via control panel or front-end RIP

Printable Area and Accuracy

Max. Paper Width 64' Min. Paper Width 12"

Left and Right Margins 0.2" (0.4" total)

Max. Printable Area 63.6"

Printer Interfaces

Includes as standard one Hi-Speed USB 2.0 (1.1 compatible) and one Gigabit Ethernet port

ONYX GamaPrint Pro RIP Requirements Server Workstation

Windows® 7, 8, Windows Vista® or Windows XP (32-bit or 64bit) 3.2GHz Intel i7 or better 6GB memory recommended **Client Workstation**

Macintosh® 10.5+, Windows 7, 8, Windows Vista or Windows XP (32-bit or 64-bit)

Operating Systems Supported

Mac® Mac OS® X, 10.8.x - 10.11.x Windows® 10, 8.1, 7 (32-bit, 64-bit)

Weight and Dimensions (W x D x H)

103" x 34" x 53" (2616 mm x 609 mm x 1346 mm)

Weight: 635 lb (288 kg)

Acoustic Noise Level

Approximately 59 dB according to ISO 7779

Temperature

Operating: 50 ° to 95 °F (10 ° to 35 °C)

Relative Humidity

Operating: 20 - 80%

Operating (recommended): 40 - 60% Storage: 5 to 85% (no condensation)

Electrical Requirements

Printer Requires two 110 V outlets Voltage AC 100 - 120 V, AC 200 - 240 V

Frequency 50 - 60 Hz

Current 20A at AC 110 - 120 V or 10 A at AC 200 - 240 V

Optional Dryer

Voltage AC 100 - 120 V, AC 200 - 240 V

Frequency 50 - 60 Hz

Current 1A at AC 110 - 120 V or 0.5 A at AC 200 - 240 V

Power Consumption

Operating Approx. 650 W or less

Standby Heaters On Approx. 520 W

Standby Heaters Off Approx. 30 W or less Power Off Less than

0.6 W or less

Sleep Mode Less than 3.5 W **ENERGY STAR®** qualified **Country of Origin** China

Ordering Information

Epson SureColor S60600 SCS60600 Ink Cleaner T699300 Printer Maintenance Kit C13S210044 Additional Waste Ink Bottle C13T724000 Additional Cleaning Cartridge T696000

UltraChrome GS3 Ink (700 mL)

Black Ink T890100 T890200 Cvan Ink Magenta Ink T890300 Yellow Ink T890400

Extended Service Plans³

Epson Preferred Plus Service Silver EPPS5070SB1 FPPS5070GB1 Epson Preferred Plus Service Gold Epson Preferred Plus Service Platinum FPPS5070PB1

Please visit us at proimaging.epson.com

1 Print times are based upon print engine speeds only. Total throughput depends upon front-end driver/RIP, file size, printing resolution, ink coverage, network speed, etc. | 2 The printer is designed to use only Epson ink cartridges and not other brands of new or refilled cartridges, or other brands of ink or bulk ink systems. Using Epson cartridges is important for reliable performance and high image quality. | 3 Note that warranty coverage for the printhead and ink delivery system is terminated if the printer is ever used with new or refilled ink cartridges, inks, or ink delivery systems other than the UltraChrome GS3 system for which the printer was designed.

Better Products for a Better Future

eco.epson.com

Epson America, Inc. 3840 Kilroy Airport Way, Long Beach, CA 90806

SmartWay

Epson Canada Limited

185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com www.epson.ca

EPSON, PrecisionCore, SureColor, TFP and UltraChrome are registered trademarks, EPSON Exceed Your Vision is a registered logomark and Better Products for a Better Future is a trademark of Seiko Epson Corporation. Mac, Mac OS and Macintosh are trademarks of Apple Inc., registered in the U.S. and other countries. Smartway is a service mark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2015 Epson America, Inc. Com-SS-Oct-13 CPD-50272 11/15

Name

Email

Phone Number

Specification Sheet | Page 2 of 2