



Product Specification Data



Description

IM3211 is an exceptional choice when you need a film to advertise on commercial grade carpet. The high-performance acrylic adhesive is tacky enough to grab the carpet fibers while still removing clean! This 3.4 mil PVC vinyl is married to a 90# lay-flat paper liner. This film is compatible with eco-solvent, solvent, latex and UV ink platforms.

Applications

This film is designed for temporary graphics on commercial grade carpet. An overlamine like OLFL-309/OLFL-311 by briteLine is required to make the graphics slip resistant.

Thickness

Film	3.4 mil
Adhesive	.8 to 1 mil
Liner	6.7 mil

Removability

Up to 6 mo from common commercial grade carpet. Commercial grade carpet has a short nap and a tight weave. Carpet should be clean prior to application.

Recommendations

Overlamine floor graphics with a UL approved overlamine to provide slip resistance. Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.

Adhesion

High performance acrylic pressure sensitive adhesive with removability. Tacky enough to grip the carpet threads while removing clean.

Temperature Ranges

Minimum application temperature	40°F
Service temperature range	-40°F to 180°F

Dimensional Stability

Good

Product Series

IM3211-54 54" x 150'

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions of sale, including disclaimer of warranties and limitation of liability.