



Product Specification Data



Description

Briteline OLFL-309 overlamine is a textured overlay film with a soft matte finish. This overlamine is 5mil thick and can be used as an inexpensive alternative to polycarbonate laminate. This laminate comes on a clear polyester liner to ensure the adhesive has a smooth and exceptionally clear coating.

Applications

This laminate is designed to provide a slip resistant and scratch resistant overlay on floor graphics, counter mats and decals.

Thickness

Film	5 mil
Adhesive	1.3 - 1.7 mil
Liner	1.5 mil

Slip Resistance

OLFL-309 is classified UL 410 for floor graphics and overlay applications.

Shelf Life

12 months shelf life when stored at 70°F and 50% relative humidity

Temperature Ranges

Minimum application temperature	40°F
Service temperature range	-40°F to 200°F

Expected Exterior Durability

This product is designed for indoor applications

Expected Indoor Durability

OLFL-309 will function as a floor overlamine for 6 months under normal conditions.

Product Series

OLFL-30954 54" x 150'

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions of sale, including disclaimer of warranties and limitation of liability.