



Dual Perf 70/30

briteline.com

Briteline Dual Perf 70/30 is a 6 mil black/white composite PVC with approx. 1.7mm perforations and a removable acrylic pressure-sensitive adhesive. This product comes with a multi-purpose release liner which is compatible with UV, Solvent, Eco-Solvent and Latex ink systems. Perforation pattern: Approx. 30% perforated, 70% retained. Exterior-mount flat window graphics intended for short-term applications (6-12 months), such as POP, retail and commercial window signage.

Applications

Designed for flat windows such as glass doors, store fronts or any other clear flat surface. When paired with a laminate to extend the durability, use an optically clear version such as Briteline optically clear lam BL-OPT54100/BL-OPT60100

Adhesive & Liner

Transparent and removable leaving minimal adhesive on the surface. The longer the graphic is applied, the more adhesive it could potentially leave behind.

The liner on Briteline Dual Perf is a combination of a punched liner and a solid liner allowing the material to be printed with solvent, latex or UV ink platforms.

Laminating

Always allow 24 hours for inks to dry and outgas before applying an overlamine. For best results, let graphics sit for 12 hours following laminating to allow the laminate adhesive to bond effectively to the window film.

Storage Stability

6-month shelf life when stored at 70°F and 50% relative humidity.

Dimensional Stability

Fair

Thickness

Film 6 mil
Liner 150 g

Recommendations

Proper surface prep is highly suggested before installation, use mild soap and warm water or isopropyl alcohol with water mixture (70% alcohol 30% water) make sure surface is completely dry and free of any debris or contaminants.

Leave a 1/4" between all edges of the window and the edge of the window perf. The vinyl should not meet any rubber or silicone edges of the window. Use the hinge method to remove the liner during installation, squeegee the film from the center of the graphic towards the edge with even pressure and consistent strokes.

Product Series

BL-DLP541007030	54" x 100'
BL-DLP601007030	60" x 100'

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions or sale, including disclaimer of warranties and limitation of liability.

Exclusively from

