



Product Specification Data



Description

Briteline® WrapCast lamination is an excellent choice to use for vehicle graphics and long term signage. It offers maximum flexibility and ultra-protection against UV radiation. The overlaminates solvent adhesive wets out quickly to provide a clean image.

Applications

Vehicle graphics
Long term signage
Window Perf (Optically Clear version only)

Features & Benefits

Gives graphics a wet paint look
Permanent solvent adhesive
Excellent protection against UV radiation, adding longevity to the underlying graphic
Ultra-flexibility

Technical Data

Film	2 mil (50 micron) thickness
Color and Finish (Thickness variance ± 10%)	Clear - gloss, satin, matte
Minimum Application Temp.	50° F
Service Temp. Range	-40° F to 175° F
Outdoor life of film	7 years
Shelf Life (temp. controlled)	2 years

Recommendations

Allow time for inkjet prints to completely outgas before applying lamination. Pair Briteline® WrapCAST laminate with Briteline® WrapCAST film.

Chemical Resistance

Distilled Water (24 hours)	No Effect
Detergent (24 hours)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (10 min)	No Effect
SAE 30 Motor Oil (10 min)	No Effect

Available Finishes

Gloss	Satin
Matte	Optically Clear (Gloss)

Available Sizes

54" x 150'
60" x 150'

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions or sale, including disclaimer of warranties and limitation of liability.